

#### **SECTION 1. IDENTIFICATION**

Product name : Spikes Special Adhesive

Product code : SSA

Manufacturer or supplier's details

Company name of supplier : Bird-X

Address : 300 N. Oakley Blvd.

Chicago, IL 60612

Telephone : (312) 226-2473

Emergency telephone : AAPCC: 1(800)222-1222

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Eye irritation : Category 2A

Skin sensitization : Category 1

Specific target organ

systemic toxicity - repeated

exposure (Oral)

: Category 2 (Blood)

**GHS Label element** 

Hazard pictograms



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs (Blood) through prolonged

or repeated exposure if swallowed.

Precautionary Statements : **Prevention:** 

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of



the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

#### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone

Sealant

### Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Silicon dioxide	7631-86-9	>= 5 - < 10
Methyltri(ethylmethylketoxime)silane	22984-54-9	>= 1 - < 5
Vinyltri (methylethylketoxime) silane	2224-33-1	>= 1 - < 5
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 0.1 - < 1
Methyltri(ethylmethylketoxime)silane isomers	Not Assigned	>= 0.1 - < 1
and oligomers		

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.



Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides Silicon oxides Formaldehyde Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.



#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: Use personal protective equipment. tive equipment and emergency procedures

Follow safe handling advice and personal protective equip-

ment recommendations.

**Environmental precautions** : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

> Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents



#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

### Hazardous components without workplace control parameters

Ingredients	CAS-No.
Methyltri(ethylmethylketoxime)	22984-54-9
silane	
Vinyltri (methylethylketoxime)	2224-33-1
silane	
N-(3-	1760-24-3
(Trimethoxysilyl)propyl)ethylen	
ediamine	
Methyltri(ethylmethylketoxime)	Not Assigned
silane isomers and oligomers	

# Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl methyl ketoxime	96-29-7	TWA	10 ppm	DCC OEL
Further information: Skin sensitization				
		TWA	10 ppm	US WEEL

# **Engineering measures**

: Processing may form hazardous compounds (see section

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

#### Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled



release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may re-

quire added precautions.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : colorless

Odor : slight

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point

Initial boiling point and boiling

range

No data availableNot applicable

Flash point : Not applicable



Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.04

Solubility(ies)

Water solubility
Partition coefficient: n-

octanol/water

: No data available

: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability

Possibility of hazardous reac-

tions

: Stable under normal conditions.

: Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

Water



Hazardous decomposition products

Contact with water or hu-

: Ethyl methyl ketoxime

mid air

Thermal decomposition : Formaldehyde

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Skin contact Ingestion Eye contact

# **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Ingredients:** 

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Information taken from reference works and the

literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Information taken from reference works and the

literature.

Methyltri(ethylmethylketoxime)silane:

Acute oral toxicity : LD50 (Rat): > 2,520 mg/kg

Assessment: The substance or mixture has no acute oral tox-

city

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-



.

icity

Remarks: Based on test data

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on test data

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 (Rat): 2,295 mg/kg

Remarks: Based on test data

Acute inhalation toxicity : LC50 (Rat): > 1.49 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Remarks: Based on test data

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on test data

# Skin corrosion/irritation

Not classified based on available information.

#### **Ingredients:**

# Silicon dioxide:

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

# Methyltri(ethylmethylketoxime)silane:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

### N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species: Rabbit

Result: Mild skin irritation Remarks: Based on test data

### Serious eye damage/eye irritation

Causes serious eye irritation.

# **Ingredients:**

# Silicon dioxide:

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

# Methyltri(ethylmethylketoxime)silane:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Remarks: Based on test data



### Vinyltri (methylethylketoxime) silane:

Species: Rabbit

Result: Irreversible effects on the eye

Remarks: Based on test data

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species: Rabbit

Result: Irreversible effects on the eye

Remarks: Based on test data

#### Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days Remarks: Based on data from similar materials

### Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

# Ingredients:

Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitising effect.

Information taken from reference works and the literature.

# Methyltri(ethylmethylketoxime)silane:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Based on test data

### Vinyltri (methylethylketoxime) silane:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.
Based on data from similar materials

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.

Information taken from reference works and the literature.

### Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Assessment: Probability or evidence of skin sensitization in humans



Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.
Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

**Ingredients:** 

Silicon dioxide:

Genotoxicity in vitro : Result: negative

Remarks: Information taken from reference works and the

literature.

Genotoxicity in vivo : Application Route: Ingestion

Result: negative

Remarks: Information taken from reference works and the

literature.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

### Methyltri(ethylmethylketoxime)silane:

Genotoxicity in vitro : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)

Result: negative

Remarks: Based on test data

### Vinyltri (methylethylketoxime) silane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on test data

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on test data

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

# Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.



NTP

# SPIKES SPECIAL ADHESIVE

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

**Ingredients:** 

Methyltri(ethylmethylketoxime)silane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: No effects on fertility. Remarks: Based on test data

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: Based on test data

Reproductive toxicity - As-

sessment

: No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Application Route: Ingestion Symptoms: No effects on fertility. Remarks: Based on test data

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: Based on test data

Reproductive toxicity - As-

sessment

: No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Blood) through prolonged or repeated exposure if swallowed.

**Ingredients:** 

Methyltri(ethylmethylketoxime)silane:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to



.....

100 mg/kg bw.

### Vinyltri (methylethylketoxime) silane:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

#### N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg

bw or less.

### Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

### Repeated dose toxicity

#### **Ingredients:**

# Methyltri(ethylmethylketoxime)silane:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on test data

#### Vinyltri (methylethylketoxime) silane:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on data from similar materials

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Application Route: Ingestion Remarks: Based on test data

#### Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on data from similar materials

### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

### **Product:**

Remarks: During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumor rates.



#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Ingredients:**

# Methyltri(ethylmethylketoxime)silane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials : EC50 (Daphnia magna (Water flea)): > 120 mg/l

Toxicity to daphnia and other

aquatic invertebrates

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 94 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

**Ecotoxicology Assessment** 

Acute aquatic toxicity : This product has no known ecotoxicological effects.

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 597 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia sp.): 81 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 8.8 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 3.1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia sp.): > 1 mg/l

Exposure time: 21 d

Toxicity to bacteria : EC50 (Pseudomonas putida): 67 mg/l

Exposure time: 16 h
Test Type: Growth inhibition

Method: DIN 38 412 Part 8



### Persistence and degradability

### **Ingredients:**

# Methyltri(ethylmethylketoxime)silane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 14.5 % Exposure time: 21 d

Method: OECD Test Guideline 302B

Remarks: Based on data from similar materials

# Vinyltri (methylethylketoxime) silane:

Biodegradability : Result: Not readily biodegradable.

Stability in water : Degradation half life: 1 s

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 39 %

Method: OECD Test Guideline 301A

Stability in water : Degradation half life: 0.025 h (24.7 °C) pH: 7

Method: OECD Test Guideline 111

# **Bioaccumulative potential**

# **Ingredients:**

### Methyltri(ethylmethylketoxime)silane:

Partition coefficient: n- : log Pow: 11.2

octanol/water

# N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Partition coefficient: n-

octanol/water

: log Pow: -0.3

### Mobility in soil

No data available

# Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDER ATIONS**

#### **Disposal methods**

Resource Conservation and

Recovery Act (RCRA)

: This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste han-



dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulation**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

# **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know**

# **CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
n-Hexane	110-54-3	5000	*
Methanol	67-56-1	5000	*
Ethylenediamine	107-15-3	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethylenediamine	107-15-3	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



# **US State Regulations**

Vinyltri (methylethylketoxime) silane

# Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 - 10 %
Methyltri(ethylmethylketoxime)silane	22984-54-9	1 - 5 %
New Jersey Right To Know		
Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 - 10 %
Methyltri(ethylmethylketoxime)silane	22984-54-9	1 - 5 %

California Prop 65 WARNING: This product contains a chemical known in the

2224-33-1

State of California to cause birth defects or other reproductive

1 - 5 %

harm.

Methanol 67-56-1

# The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or

exempted from listing on the TSCA Inventory of Chemical

Substances.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

#### **Inventories**


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)



#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

#### Full text of other abbreviations

DCC OEL : Dow Corning Guide

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

: USA. Workplace Environmental Exposure Levels (WEEL) US WEEL

DCC OEL / TWA : Time weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA Z-3 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

Sources of key data used to

compile the Material Safety

**Data Sheet** 

**Revision Date** 04/04/2015

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.



US / Z8