

PULSE SMT-01 CFU

Bird Repellent System | Insulated Wire System Technical Specification Sheet

Patent Pending | Model SMT-01 | Version 1.0

Control Hub	
Measurements	9" x 6" x 4" / 23 x 15.24 x 10.14 cm (L x W x H)
Weight	6 lb / 2.72 kg
Enclosure Material	Polycarbonate
Out Frequency	120-500 Hz ¹
Power Consumption	35 Watts
Rated Voltage	110 / 220–240 Volts
Current	20 mA/ 40 mA ²
Operation Voltage	2,500 Volts
Temperature Rating	-40°C to 130°C / -40°F to 266°F
Maximum Coverage	Up to 600 linear ft ³ / 180 linear m (per system)
Mounting	4 mounting holes, max screw size 5/16 in or M8
Orientation	Mounted vertically with outlets facing downward



¹Output frequency controlled via dial.

²20mA corresponds to International power plugs & 40mA corresponds to NA power plug

³Quantity of five 100 ft emitter lines are shipped per control Hub. Additional emitter lines can be purchased separately.

Emitter Line	
Length (per roll)	Qty 5 (100 ft) / 30.48 m
Material	XLPE sheathing with copper conductor
Rated Voltage	3,000 V
Colors	Dark Grey and Light Grey
Gauge	14 AWG



End Cap

Measurements	22 mm OD
Weight	0.1 lb / 0.045 kg
Qty per 100 ft	6 pcs
Material	Polycarbonate

**Post Supports**

Measurements	8" x 3" x 5" / 20 x 8 x 13 cm
Weight	1.14 lb / 0.5 kg
Qty per 100ft	1pk/100' (5 packs included with ea. system)
Material	Polycarbonate
Mounting Options	Screw or magnet

**Line Extenders (Male / Female)**

Measurements	2.72 x 0.77 in. / 69 x 19.5 mm
Qty per 100 ft	5 each, 10 total
Material	Plastic
Ratings	UL 94V-0 & IP65

**Branching Connector (Y-Connector)**

Measurements	2.32 x 1.50 x 0.70 in. / 59 x 38 x 17 mm
Qty per 100 ft	5 each, 10 total
Material	Plastic
Ratings	UL 94V-0 & IP65
Max Branch Length	15 ft / 4.6 m per section



Male / Female Crimp Bushings		
Measurements	0.22" x 1.14" / 5.5 x 29 mm	
Qty per 100 ft	5 each, 10 total	
Material	Tin-coated copper alloy	

Pulse CFU						
Family	Control Hub Version	Voltage	Wire Type	Wire Color	Wire Length ¹	Stand
SMT-01	-C=Controlled Frequency Unit	-1 =120NA	-P = Pulse (insulated)	LG =Light Grey	5 = 500ft	-P = Post (insulated)
		-2 =220EU		DG =Dark Grey		-MP = Magnetic Post (\$400 adder)
		-3 =230UK		BL =Black		
		-4 =240AU				

Example: SMT-01-C-1-PLG5-P

¹Insulated Wire ships in (5) 100ft increments

Accessories Sold Separately

Signal Detector		
Weight	0.21 lb / 0.1 kg	
Batteries Included	N/A- Rechargeable	
Detection V/m limit	Up to 2000 V/m	

Crimp Plier		
Weight	1.25 lb / 0.56 kg	
Crimp Sizes	Suitable for three crimp sizes	

Certifications & Compliance

UL | CSA | IP65 (Control Hub) | IP66 (Connectors) | UL 94V-0 (Line Extenders & Branching Connectors)

Regional variants available: North America (110V~, 60Hz), UK (220V~, 50Hz), EU (230V~, 50Hz), AU/NZ (240V~, 50Hz)

Warranty

24-month warranty from date of shipment. Contact solutions@bird-x.com for claims.

Contact Information

Bird-X, Inc.

845 N Larch Avenue, Suite 2, Elmhurst, IL 60126 – USA

Web: www.bird-x.com | Support: solutions@bird-x.com